

Rope ladder

Rope ladders are custom made by our skilled workmen in any type and measure. We produce rope ladders for playgrounds, as for escape routes as for industrial applications.

Standard rope ladder

The standard rope ladder is frequently used for escape routes as for several climbing applications. The ladder has two Polytex side ropes. Polytex is a high quality polypropylene with extra U.V.-stabilizer. Please find in the schedule below the details of this rope.

Shock load	Good
Handiness	Good
Durability	Good
Rot proof	Excellent
UV-resistance	Excellent
Resistance to acids	Excellent
Alkali resistance	Excellent
Abrasion resistance	Reasonable
How to storage	Wet / dry
Buoyancy	Floats
Melting point	Approx. 165°C
Breaking load Polytex	2.975 kg



Every rung is made of ash-wood and is spaced at approximately 32 centimetres. Every rung is secured in such a manner that it remains horizontal. The diameter of the rung is 36mm, the width of the rung is 40 centimetres. To assemble the rope ladder our skilled workmen have spliced two thimbles on top of the rope ladder.

<i>Length</i>	<i>Article number</i>
3.00 meter	BS.22.04.02.30
3.50 meter	BS.22.04.02.35
4.00 meter	BS.22.04.02.40
4.50 meter	BS.22.04.02.45
5.00 meter	BS.22.04.02.50
5.50 meter	BS.22.04.02.55
6.00 meter	BS.22.04.02.60
6.50 meter	BS.22.04.02.65
7.00 meter	BS.22.04.02.70
7.50 meter	BS.22.04.02.75
8.00 meter	BS.22.04.02.80
8.50 meter	BS.22.04.02.85
9.00 meter	BS.22.04.02.90
9.50 meter	BS.22.04.02.95
10.00 meter	BS.22.04.02.1000